BruntonShaw
STRENGTH IN SERVICE

A Division of Usha Martin UK Limited

Sandy Lane, Worksop,
Nottinghamshire, UK S80 3ES
Tel: +44 (0)1909 537600
Fax: +44 (0)1909 500199
e-mail: info@brunton-shaw.co.uk

A18208/1

TEST CERTIFICATE

Customer

USHA MARTIN UK LIMITED
5 BLAIR COURT
CLYDEBANK BUSINESS PARK
GLASGOW.
LANARKSHIRE
G81 2LA

Customer Order No. 11454

Certificate No.	263884/3/5	**BSUK Order No.**	263884
Reel No.	8987	**BSUK Part No**	111263
Code No.	A18208/1		
Applied Standard	OTIS Specification 51111/2003		
Nominal Diameter:	6.3MM		
Construction:	6X19S		
Lay:	RHOL		
Core:	FIBRE		
Nominal Tensile Strength:	1960 Newton/mm2		
Surface Finish:	GalVd		
Lubrication:	OIL		
Length:	2900M		
Miniumum Breaking Force (kN)	21.2		

Measured Diameter off tension (mm)	6.58
Measured Diameter at 10% of MBL (mm)	6.49
Lay Length off tension (mm)	41.5
Measured Breaking Force (kN)	29.6
Measured Constructional Stretch %	0.18

Signed:

Date: 22.11.10

R. Dews

On behalf of Brunton Shaw UK
Certificate according to EN10204 type 3.1.

Manufactured under an ISO 9001:2000
Quality System Registered by BSI.
Reg. No. FM 01267